

CUSTOMER

KINNECOTT ENERGY

LOCATION

GILLETTE, WY USA / 2009

EOUIPMENT

COAL LOADING GATE

APPLICATION

GEARBOX LUBE OIL

PROVEN RESULTS



EXTENDED
LUBE-OIL
AND
GEARBOX
OPERATING LIFE

CHALLENGE

Silo gearboxes controlling the shoot gates that load the trains with coal had inadequate filtration that only captured contamination down to 20 microns in size. Kinnecott Energy required an OEI magnetic filter to capture wear contamination down to 4 microns and below to reduce premature wear of bearings and other close tolerance components.

SOLUTION

Install an OEI ADD-Vantage 9000 in the gearbox. The ADD-Vantage 9000 includes OEI's patented magnetic filter element as well as a stainless steel cloth element. The "inside-out" flow control design operates with the magnetic filter element as the primary filter. The high holding capacity allows for extended operating life of the stainless steel cloth element which minimizes by-passing and extends cleaning intervals



A significant amount of ferrous and non-ferrous contamination was captured by OEI magnetic elements. This system has proven to surpass traditional filtration and extend both lube oil and gearbox life.



PRODUCT RECOMMENDATION

ADD-VANTAGE 9000













403.242.4221



QUOTES@ONEEYEINDUSTRIES.COM

